

ZCS2080G3



ZCS2080G3AB



ZCS2080G3PCB



ZCS2080G3PVDSB

SPECIFICATION

- Grade 201 stainless steel
- 52mm x 8mm push-on sprung rose
- Heso spindle
- Supplied with bolt through & wood screw fixings
- Suitable for 35-54mm doors
- Successfully fire tested in accordance with the requirements of BS EN 1634-1, suitable for use on 30 and 60 minute timber fire doors
- Complies to the design requirements of BS 8300-2:2018
- Successfully mechanically tested in accordance with the requirements of BS EN 1906 : 2010, achieving Grade 3 Category of Use.

3	7	-	B	0	4	0	B

BS EN 1906 : 2010 Grade 3


SUITABILITY



STANDARDS



TECHNICAL



CODE	DESCRIPTION	FINISH
ZCS2080G3AB	22mm tubular return to door lever on round rose - 52mm x 8mm push-on rose - Grade 201	Antique Brass
ZCS2080G3PCB	22mm tubular return to door lever on round rose - 52mm x 8mm push-on rose - Grade 201	Powder Coated Black
ZCS2080G3PVDSB	22mm tubular return to door lever on round rose - 52mm x 8mm push-on rose - Grade 201	PVD Satin Brass
<div style="display: flex; justify-content: space-between; align-items: flex-start;"> <div style="text-align: center;"> </div> <div> <p>For more information please contact us today: ERA Home Security T/A Zoo Hardware, Unit B, Dukes Drive, Kingmoor Park North, Carlisle, Cumbria CA6 4SH</p> <p>Call: 01228 672900 Fax: 01228 672928 Email: sales@zoo-hardware.co.uk Web: www.zoohardware.co.uk</p> </div> <div style="text-align: center;"> </div> </div>		