

ZCS2040G3



ZCS2040G3AB



ZCS2040G3PCB



ZCS2040G3PVDSB

SPECIFICATION

- Grade 201 stainless steel
- 52mm x 8mm push-on sprung rose
- Heso spindle
- Supplied with bolt through & wood screw fixings
- Suitable for 35-54mm doors
- Successfully fire tested in accordance with the requirements of BS EN 1634-1, suitable for use on 30 and 60 minute timber fire doors
- Successfully mechanically tested in accordance with the requirements of BS EN 1906 : 2010, achieving Grade 3 Category of Use.

3	7	-	B	0	4	0 B

BS EN 1906 : 2010 Grade 3


SUITABILITY



STANDARDS



TECHNICAL



CODE	DESCRIPTION	FINISH
ZCS2040G3AB	19mm arched lever on round rose - 52mm x 8mm push-on rose - Grade 201	Antique Brass
ZCS2040G3PCB	19mm arched lever on round rose - 52mm x 8mm push-on rose - Grade 201	Powder Coated Black
ZCS2040G3PVDSB	19mm arched lever on round rose - 52mm x 8mm push-on rose - Grade 201	PVD Satin Brass



For more information please contact us today:

ERA Home Security T/A Zoo Hardware,
Unit B, Dukes Drive, Kingmoor Park North,
Carlisle, Cumbria CA6 4SH

Call: 01228 672900
Fax: 01228 672928
Email: sales@zoo-hardware.co.uk
Web: www.zoohardware.co.uk

