

TECHNICAL SPECIFICATION SHEET

ZPS006iSS-HEX



In an emergency, the key is also equipped with a 5mm drive to be able to operate a bathroom lock follower.

SPECIFICATION	SUITABILITY	TECHNICAL
<ul style="list-style-type: none"> • Rose diameter: 50mm • Rose projection: 8mm • Spindle size: 5mm • Disabled turn • SS 304 Grade material • Screw on stainless steel outer rose • Also supplied with 20mm wood screws • Fire tested suitable for 30 & 60 min timber doors • Requires hex key ZCS000-HEX-KEY (sold seperately) 	<p>Suitable for DOMESTIC and COMMERCIAL use.</p> <p>STANDARDS</p> <p>BS EN 1634 30190</p>	

Only recommended for use with ZOO DIN Locks.
If other locks are required please check for compatibility.

DfE Technical Annex 2D

The Hex release version is available for use in applications that are relevant to the Department for Education Technical Annex 2D: Internal Elements and Finishes. Part 5.2.2.

Part C. refers to Bathroom Locks and states: Bathroom Lock - Lock that can be locked from the inside by turn or lever and can be released from outside by hexagon or star key (not coin-slot).

CODE	DESCRIPTION	FINISH
ZPS006iSS-HEX	Disabled turn and hex release with indicator	Satin Stainless
<p>For more information please contact us today: ERA Home Security T/A Zoo Hardware, Unit B, Dukes Drive, Kingmoor Park North, Carlisle, Cumbria CA6 4SH</p> <p>Call: 01228 672900 Fax: 01228 672928 Email: sales@zoo-hardware.co.uk Web: www.zoohardware.co.uk</p>		<p>FM 668401 EMS 668402</p>