

ZDL7260LL Series

DIN lift to lock - 72mm c/c - backset 60mm



ZDL7260LLSS



ZDL7260LL-PCB



ZDL7260LL-PCW



ZDL7260LL-PVDBZ



ZDL7260LL-PVDSB

PRODUCT FEATURES

- 60mm backset
- Square & radius profile forends
- 22mm SS304 forend
- SS304 latch & deadbolt
- Anti-rattle strike
- Grip tight follower
- Blind escutcheon & emergency release half set
- BS EN 12209 : 2002 Grade 3

										
3	C	8	1	0	G	-	B	G	2	0

FIRE TESTING

- Successfully fire tested in accordance with the requirements of BS EN1634-1, suitable for use on 30, 60, 90 and 120 minute timber fire doors, and 30, 60, 90, 120 and 240 minute steel fire doors

CERTIFICATION

- UKCA marked (Certificate AG7885)
- CE marked (Certificate AG5123)
- CERTIFIRE approved (Certificate CF850)



1121-CPR-UK-AG7885



2812-CPR-AG5123




APPROVED
CF850

FOREND OPTIONS

- Square
- Radius

TECHNICAL



CODE	DESCRIPTION	FINISH
ZDL7260LL-PCB	DIN lift to lock - 72mm c/c - backset 60mm	Powder Coat Black
ZDL7260LL-PCW	DIN lift to lock - 72mm c/c - backset 60mm	Powder Coat White
ZDL7260LL-PVDBZ	DIN lift to lock - 72mm c/c - backset 60mm	PVD Bronze
ZDL7260LL-PVDSB	DIN lift to lock - 72mm c/c - backset 60mm	PVD Satin Brass
ZDL7260LLSS	DIN lift to lock - 72mm c/c - backset 60mm	Satin Stainless
ZDL7260RLSS	DIN lift to lock - 72mm c/c - backset 60mm - radius	Satin Stainless
 For more information please contact us today: ERA Home Security T/A Zoo Hardware, Unit B, Dukes Drive, Kingmoor Park North, Carlisle, Cumbria CA6 4SH Call: 01228 672900 Fax: 01228 672928 Email: sales@zoo-hardware.co.uk Web: www.zoohardware.co.uk		 ISO 9001 Quality Management Systems CERTIFIED ISO 14001 Environmental Management CERTIFIED FM 668401 EMS 668402