

TECHNICAL SPECIFICATION SHEET

ZCS004iSS-HEX



ZCS004iSS-HEX

In an emergency, the key is also equipped with a 5mm drive to be able to operate a bathroom lock follower.

SPECIFICATION	SUITABILITY	TECHNICAL
<ul style="list-style-type: none"> Rose diameter: 52mm Rose projection: 8mm Spindle size: 5mm Standard turn SS 304 Grade material Push on stainless steel outer rose Also supplied with 20mm wood screws Fire tested suitable for 30 & 60 min timber doors Requires hex key ZCS000-HEX-KEY (sold seperately) <p>Accessories available: ZFP01S - Additional fixing pack – complete with bolt fixings SP25 - 5mm x 65mm spindle</p>	 STANDARDS 	

DfE Technical Annex 2D
The Hex release version is available for use in applications that are relevant to the Department for Education Technical Annex 2D: Internal Elements and Finishes. Part 5.2.2.
Part C. refers to Bathroom Locks and states: Bathroom Lock - Lock that can be locked from the inside by turn or lever and can be released from outside by hexagon or star key (not coin-slot).

CODE	DESCRIPTION	FINISH
ZCS004iSS-HEX	Turn and hex release with indicator	Satin Stainless
<p>For more information please contact us today: ERA Home Security T/A Zoo Hardware, Unit B, Dukes Drive, Kingmoor Park North, Carlisle, Cumbria CA6 4SH</p> <p>Call: 01228 672900 Fax: 01228 672928 Email: sales@zoo-hardware.co.uk Web: www.zoohardware.co.uk</p>		<p>FM 668401 EMS 668402</p>