ZS-ALP100 Series

Anti-ligature Pull Handle

10-03-25 V2.1

PRODUCT FEATURES

- **Length:** 150mm
- **Width:** 44mm
- **Projection:** 34mm
- **Centres:** 100mm
- **Material:** Grade 304 Stainless Steel
- Security bolt fixings supplied
- BF = Bolt-fix single side
- GS = Grub screw side to make up back-to-back set

FIRE TESTING

- Successfully fire tested in accordance with the requirements of BS EN 1634-1, suitable for use on timber fire doors upto 30 and 60 minutes

ANTI-LIGATURE TESTING

- Independently tested in accordance with DHF Technical Specification TS001:2013 Enhanced Requirements & Test Methods for Anti-Ligature Hardware and passed with the highest rating: A4 – 0.5mm ligature

TECHNICAL

44.2   34.0

150

34.0

PLEASE NOTE

For a back-to-back pair, please order both ZS-ALP100BF-SSS & ZS-ALP100GS-SSS to create a back-to-back set.

ZS-ALP100BF-SSS   ZS-ALP100GS-SSS

CODE	DESCRIPTION	FINISH
ZS-ALP100BF-SSS	Anti-ligature pull handle - Bolt-fix single	Satin Stainless
ZS-ALP100GS-SSS	Anti-ligature pull handle - Back-to-back fix half set	Satin Stainless

ZOO
ARCHITECTURAL HARDWARE

bsi

ISO 9001 Quality Management Systems CERTIFIED	ISO 14001 Environmental Management CERTIFIED
FM 668401	EMS 668402