TECHNICAL SPECIFICATION SHEET

RT030-MINI





RT030-MINI-PCB

• Innovative magnetic stainless steel 2 part rose system



RT030-MINI-PCW

RT030-MINI-PVDSB



RT030-MINI-PVDBZ

RT030-MINI-PVDBLK



RT030-MINI-AB

TECHNICAL 32.0 3.0 63.0

• 32mm x 3mm round un-sprung mini-rose • 32mm x 3mm squircle rose also available • Screwless installation, supplied with instructions • Complies with the design requirements of BS8300

If tubular latches are required, we recommend ordering the **'SP-RT-MINIOI**' - **'Rosso Mini Spare Spindle for use with Tubular Latches'** to ensure smooth and reliable operation.

SUITABILITY

STANDARDS

.

Please note that, due to the un-sprung design of the RT-MINI series, budget latches are not advised. Should tubular latches be necessary, we recommend using our **ZTLKA series**.

135.0

CODE	DESCRIPTION	FINISH
RT030-MINI-PCB	Maggiore lever on 32mm round mini rose	Powder Coated Black
RT030-MINI-PCW	Maggiore lever on 32mm round mini rose	Powder Coated White
RT030-MINI-PVDBZ	Maggiore lever on 32mm round mini rose	PVD Bronze
RT030-MINI-PVDSB	Maggiore lever on 32mm round mini rose	PVD Satin Brass
RT030-MINI-PVDBLK	Maggiore lever on 32mm round mini rose	PVD Black
RT030-MINI-AB	Maggiore lever on 32mm round mini rose	Antique Brass
ZOO ARCHITECTURAL HARDWARE	For more information please contact us today: ERA Home Security T/A Zoo Hardware, Unit B, Dukes Drive, Kingmoor Park North, Carlisle, Cumbria CA6 4SH Call: 01228 672900 Fax: 01228 672928 Email: sales@zoo-hardware.co.uk Web: www.zoohardware.co.uk	ISO 9001 Qualty Management Systems CERTIFIED FM 668401 EMS 668402

• Grub screw on underside of lever • NO plastic packaging

SPECIFICATION



• Suitable for 35-54mm doors

For optimal performance, un-sprung lever sets such as the **RT-MINI series** should be paired with full-sized locks or latches featuring **'Grip Tight Followers'**, such as those from our ZDL, VDL, and ZUK ranges

31-03-25 V1.0