TECHNICAL SPECIFICATION SHEET



RT040-SLIM



RT040-SLIM-PVDBZ





RT040-SLIM-PCW





RT040-SLIM-AB

RT040-SLIM-PVDBLK




RT040-SLIM-PVDSB

SPECIFICATION

- Stainless Steel Push-on Rose
- 53mm x 4mm round sprung rose
- SS304 stainless steel
- 6 point fixing inner rose
- Supplied with bolt through & wood screw fixings
- Suitable for 35-54mm doors
- Improved allen key for easier installation
- Grub screw on underside of lever
- NO plastic packaging
- Successfully fire tested in accordance with the requirements of BS EN 1634-1, suitable for use on timber fire doors up to 60 minutes when combined with the ZIRTS30/60G intumescent Kit (included with each lever set)

SUITABILITY





TECHNICAL

STANDARDS





CODE	DESCRIPTION	FINISH
RT040-SLIM-PCB	Varese lever on 4mm round slim sprung rose	Powder Coated Black
RT040-SLIM-PCW	Varese lever on 4mm round slim sprung rose	Powder Coated White
RT040-SLIM-PVDBZ	Varese lever on 4mm round slim sprung rose	PVD Bronze
RT040-SLIM-PVDSB	Varese lever on 4mm round slim sprung rose	PVD Satin Brass
RT040-SLIM-PVDBLK	Varese lever on 4mm round slim sprung rose	PVD Black
RT040-SLIM-AB	Varese lever on 4mm round slim sprung rose	Antique Brass



For more information please contact us today:

ERA Home Security T/A Zoo Hardware, Unit B, Dukes Drive, Kingmoor Park North, Carlisle, Cumbria CA6 4SH

Call: 01228 672900 Fax: 01228 672928

Email: sales@zoo-hardware.co.uk Web: www.zoohardware.co.uk

