TECHNICAL SPECIFICATION SHEET



ZCS004iSS-HEX



In an emergency, the key is also equipped with a 5mm drive to be able to operate a bathroom lock follower.

SPECIFICATION

• Rose diameter: 52mm • Rose projection: 8mm

• Spindle size: 5mm Standard turn

- SS 304 Grade material
- Screw on stainless steel outer rose
- Also supplied with 20mm wood screws
- Fire tested suitable for 30 & 60 min timber doors
- Requires hex key ZCS000-HEX-KEY (sold seperately)


SUITABILITY



STANDARDS



TECHNICAL



DfE Technical Annex 2D

The Hex release version is available for use in applications that are relevant to the Department for Education Technical Annex 2D: Internal Elements and Finishes. Part 5.2.2.

Part C. refers to Bathroom Locks and states: Bathroom Lock - Lock that can be locked from the inside by turn or lever and can be released from outside by hexagon or star key (not coin-slot).

CODE	DESCRIPTION	FINISH
ZCS004iSS-HEX	Turn and hex release with indicator	Satin Stainless
	For more information please contact us today:	

ARCHITECTURAL HARDWARE

ERA Home Security T/A Zoo Hardware, Unit B, Dukes Drive, Kingmoor Park North, Carlisle, Cumbria CA6 4SH

Call: 01228 672900 Fax: 01228 672928

Email: sales@zoo-hardware.co.uk Web: www.zoohardware.co.uk



CERTIFIED

ISO 14001 Environmental Management CERTIFIED

FM 668401

EMS 668402