



VDC0036A Series

Overhead Door Closer











PRODUCT FEATURES

- Power size: Power size 3-6 (size 3 by template position size 4, 5 and 6 by template position/spring adjustment)
- Body material: Aluminium
- Arm set type / material: Scissor / Steel
- Tested functions: Closing speed, latching speed
- Non-tested functions: Backcheck / delayed action NOTE: Backcheck / Delayed action are suitable for use on non-fire rated doors only
- Maximum door weight: 120kgs (door mount pull) 100kgs (door mount push, frame mount push)
- Maximum door width: 1400mm (door mount pull)
 1250mm (door mount push, frame mount push)
- Performance Testing: Successfully tested in accordance with the requirements of BS EN1154: 1997

Classification: Door mount pull (Fig 1)

	4	8	6 3	1	1	3	
Classification: Door mount push (Fig 6),							

FIRE TESTING

 Successfully fire tested in accordance with the requirements of BS EN1634-1, suitable for use on 30, 60, 90 and 120 minute timber fire doors

CERTIFICATION

- UKCA marked (Certificate AD7958)
- CE marked (Certificate AD7917)
- CERTIFIRE approved (Certificate CF5549)







COVER OPTIONS

• Semi-radiused

FINISHES

- Silver (SE)
- Satin Stainless Steel (SSS)

CODE	DESCRIPTION	FINISH	
VDC0036A2-NC-SE	Overhead door closer, power selectable/adjustable 3-6, matching arm set / trimplate cover	Silver (SE)	
VDC0036A2-SE	Overhead door closer, power selectable/adjustable 3-6, matching arm set and semi radiused cover	Silver (SE)	
VDC0036A2-SSS	C0036A2-SSS Overhead door closer, power selectable/adjustable 3-6, matching arm set and semi radiused cover		
VIEC	For more information please contact us today: ERA Home Security T/A Zoo Hardware, Unit B, Dukes Drive, Kingmoor Park North, Carlisle, Cumbria CA6 4SH Call: 01228 672900 Fax: 01228 672928 Email: sales@zoo-hardware.co.uk Web: www.zoohardware.co.uk	ISO 9001 Qualty Management Systems CERTIFIED FM 668401 EMS 668402	